



SAFFIL BLANKET CHEMICAL SAFETY DATA SHEET

JANUARY 2001

1. IDENTIFICATION OF THE SUBSTANCE /PREPARATION AND COMPANY/ UNDERTAKING

PRODUCT NAME: 'SAFFIL' BLANKET

Address/Phone No. : Saffil Limited
Pilkington-Sullivan Site
Tanhouse Lane
Widnes
Cheshire WA8 0RY
+ 44 (0) 151 422 6700

Emergency Phone No. : IN AN EMERGENCY DIAL 999
For specialist advice in an emergency telephone +44(0) 151 422 6700

2. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT DESCRIPTION

'Saffil' alumina fibre densified by stitching with polymer.

Polymer content : 3 - 15 % w/w.
Alternative names : Alumina fibre
Chemical composition : Aluminium (III) oxide 96-97%
: Silica 3-4%
EEC No. : 215-691-6

HAZARDOUS INGREDIENT(S)	CAS No.	Symbol	R Phrases
-------------------------	---------	--------	-----------

Contains no Hazardous Ingredients in accordance with EC Directive 93/112/EEC

3. HAZARDS IDENTIFICATION

Low toxicity

May cause transient irritation of the skin, nose and throat.

This product contains organic polymer. The polymer is a combustible solid and in the presence of excessive heat or flame, can melt and burn. Burning polymer is accompanied by melting and dripping which may ignite adjacent combustible material. Molten polymer will adhere to the skin causing deep thermal burns.



4. FIRST-AID MEASURES

- Inhalation : Remove patient from exposure.
- Skin Contact : Remove contaminated clothing. Wash skin with water. If symptoms (irritation or blistering) persist obtain medical attention. Contaminated clothing should be laundered before reissue to remove this substance.
In the event of contact with molten polymer: Molten material can cause severe burns. Do NOT try to peel molten polymer from the skin. Cool rapidly with water. Obtain immediate medical attention.
- Eye Contact : Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 10 minutes. Obtain medical attention.
- Ingestion : Do not induce vomiting. Wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Obtain medical attention if ill effects occur.

Further Medical Treatment

Unlikely to be required but if necessary treat symptomatically.

5. FIRE-FIGHTING MEASURES

This product contains organic polymer. The polymer is a combustible solid and in the presence of excessive heat or flame can melt and burn. Burning polymer is accompanied by melting and dripping which may ignite adjacent combustible material. Combustion or thermal decomposition will evolve toxic and irritant vapours. See Also section 10.

Extinguishing Media: water spray, dry powder or foam.

Fire Fighting Protective Equipment: A self-contained breathing apparatus and suitable protective clothing must be worn in fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Ensure suitable personal protection (including a suitable dust mask) during removal of spillages. Protect against dust. Collect using a high efficiency vacuum cleaner.

If vacuum cleaner is unavailable: Moisten spillages with water. Clear up spillages. Transfer to a lidded container for disposal.

7. HANDLING AND STORAGE

7.1 HANDLING

Atmospheric concentrations should be minimised and kept as low as reasonably practicable below the occupational exposure limit.

After handling it is recommended that exposed areas of skin are rinsed with water.

Avoid contact with naked flames and hot surfaces as the polymer may melt and burn, releasing toxic and irritant vapours.

Provide adequate ventilation if fumes or vapours are likely to be evolved.

7.2 STORAGE

Packaging should be kept closed and intact to reduce the possibility of releasing dust.



8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Wear suitable protective clothing, gloves and eye/face protection. Loose fitting longed sleeved clothing is recommended. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

A suitable dust mask should be worn if exposure to levels above the occupational exposure limit is likely. The selection of a suitable mask will depend upon the likely atmospheric concentration and the performance data of the mask. Check with protective equipment manufacturer's data. Contaminated clothing should be laundered before reissue to remove this substance.

Occupational Exposure Limits

HAZARDOUS INGREDIENT(S)	LTEL 8hr TWA ppm	LTEL 8hr TWA mg/m ³	STEL ppm	STEL mg/m ³	Notes
Man-made Mineral Fibre	-	5	-	-	MEL

In addition to the MEL specified above, Man Made Mineral Fibre is also subject to a MEL of 2 fibres/ml.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Alumina fibre
Colour	: white
Odour	: odourless
Melting Point	: >2000 (Deg C)
Density	: 3.3 (g/ml)
Solubility (Water)	: insoluble
Solubility (Other)	: insoluble
Bulk Density	: 0.08 - 0.10 typically (g/ml)

Additional Properties

Staple fibre in mat form. Typically median fibre diameter around 3 microns, with very low levels of fibres having a diameter less than 1 micron and greater than 6 microns.

10. STABILITY AND REACTIVITY

Hazardous Reactions: None known.

Hazardous Decomposition Product(s): Thermal decomposition of the polymer will yield toxic and irritant vapours, including carbon dioxide and carbon monoxide.



11. TOXICOLOGICAL INFORMATION

Inhalation	: Dust may be irritant to the nose and throat.
Skin Contact	: May cause skin irritation in sensitive individuals. Molten polymer will adhere to the skin causing deep thermal burns.
Eye Contact	: May cause physical irritation.
Ingestion	: Low oral toxicity. Unlikely to cause harmful effects under normal conditions of handling and use.
Long Term Exposure	: Lifetime rat inhalation studies at the maximum levels achievable have shown no evidence of lung cancer, lung fibrosis or any other adverse effect, apart from a minimal pulmonary response typical of that of a 'low toxicity dust'. A lifetime feeding study in rats has produced no evidence of any adverse effects at levels up to 2.5% in the diet. Intraperitoneal, intratracheal and intrapleural studies in rats, together with two in vitro tests, have all shown negative results with asbestos and crystalline silica as controls (where relevant) producing positive responses. The results of this extensive testing programme indicate that this material lacks one or more of the fundamental characteristics necessary for mesothelioma induction, as well as not possessing fibrogenic potential.

12. ECOLOGICAL INFORMATION

Environmental Fate and Distribution

Medium tonnage material used in open systems. Solid with low volatility. The product is essentially insoluble in water. The product has no potential for bioaccumulation. The product has no mobility in soil.

Persistence and Degradation

The product shows no evidence for biodegradability in water. The product shows no evidence for biodegradability in soil.

Toxicity

Unlikely to be hazardous to aquatic life.

Effect on Effluent Treatment

Unlikely to have any significant effects on effluent treatment.

13. DISPOSAL CONSIDERATIONS

Bury on an authorised landfill site.

Disposal should be in accordance with local, state or national legislation.

14. TRANSPORT INFORMATION

Not Classified as Hazardous for Transport.



15. REGULATORY INFORMATION

Not Classified as Dangerous for Supply/Use.

Product packaging labelling:

Handling advice - Working with this product may cause temporary irritation of the skin, nose and throat.

When Handling - Loose fitting long sleeved clothing, gloves and eye protection are recommended. If dust is generated wear a suitable dust mask.

After Handling - Rinse exposed areas of skin with water. Wash work clothes separately. Avoid contact with naked flames and hot surfaces as the polymer may melt and burn, releasing toxic and irritant vapours.

16. OTHER INFORMATION

Use: refractory material.

This data sheet was prepared in accordance with Directive 93/112/EC.

The following sections contain revisions or new statements: 1,16

'Saffil' is a trademark of Dyson Group PLC.

Information in this publication is believed to be accurate and is given in good faith, but it is for the Customer to satisfy itself of the suitability for its own particular purpose. Accordingly, Saffil Limited gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed. Any trademarks herein identified are trademarks of companies within Dyson Group PLC.

MEL: Maximum Exposure Limit (UK HSE EH40).

